



- NOTES:
1. DOOR MODEL DS3501 IS INSULATED DS-350
  2. WHEN USING LOCK BY OTHERS (LBO), LONG THROW SLIDE REQUIRED
  3. DOORS FOR OPENING SIZE GREATER THAN 10'-0" IN EITHER HEIGHT OR WIDTH USE T-BRACKET
  4. TOP DRAFT STOP INCLUDED
  5. OPER. HAND DETERMINED INSIDE LOOKING OUT
  6. CURTAIN LOCK (CTL) HAND DETERMINED OUTSIDE LOOKING IN
  7. DIMENSIONS SHOWN ARE APPROXIMATE. SEE INSTALL MANUAL FOR EXACT COMPONENT LOCATION
  8. FASTENER SUBSTITUTION MUST BE REVIEWED AND APPROVED BY FACTORY PRIOR TO INSTALL

METHOD OF OPERATION	A	B	C
PUSH-UP	6"	6'-0" TO 8'-0"	20" 10"
DIRECT DRIVE CHAIN/MOTOR	9"	8'-1/4" TO 10'-0"	22" 11"
REDUCED DRIVE CHAIN	8"	10'-1/4" TO 16'-0"	24" 12"

**WINDLOAD RATING**

MAXIMUM WIDTH	PANEL PROFILE	DESIGN PRESSURE
10'-0"	ROUND	±37PSF
	SQUARE	±44PSF
12'-0"	ROUND	±28PSF
	SQUARE	±40PSF
16'-0"	ROUND	±28PSF
	SQUARE	±34PSF

**DS-350 COMMERCIAL DOOR**

CUSTOMER NAME \_\_\_\_\_

CUSTOMER NUMBER \_\_\_\_\_

PROJECT NAME \_\_\_\_\_

PROJECT LOCATION \_\_\_\_\_

CONTACT \_\_\_\_\_

PHONE NUMBER \_\_\_\_\_

FAX NUMBER \_\_\_\_\_

DATE \_\_\_\_\_

SALES ORDER NUMBER	DOOR MODEL	QTY	EXACT OPENING SIZE WIDTH	EXACT OPENING SIZE HEIGHT	OUTSIDE CURTAIN COLOR	JAMB TYPE	METHOD OF OPERATION	OPER. HAND	OPTIONAL HOOD?	LOCK OPTIONS	OTHER OPTIONS
DS350	DS3501									ISB CTL CTL CTL LBO NONE	

PROJECT LOCATION \_\_\_\_\_

CONTACT \_\_\_\_\_

PHONE NUMBER \_\_\_\_\_

FAX NUMBER \_\_\_\_\_

DATE \_\_\_\_\_

SALES ORDER NUMBER	DOOR MODEL	QTY	EXACT OPENING SIZE WIDTH	EXACT OPENING SIZE HEIGHT	OUTSIDE CURTAIN COLOR	JAMB TYPE	METHOD OF OPERATION	OPER. HAND	OPTIONAL HOOD?	LOCK OPTIONS	OTHER OPTIONS
DS350	DS3501									ISB CTL CTL CTL LBO NONE	